This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

ASSY QTY

ASSY QTY


UNIT QTY


1 LUBRICATION TOOL


Description

B/O Part #

REVISIONS									
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED				
1		RELEASED FOR PRODUCTION.	3/23/2016	RJC	JAG				








Material

DELRIN/ACETRON GP



PG.

B/O INFORMATION OR SPECIFICATIONS

NOTE: REF. BELL WORKAID FOR LUBRICATION OF TAIL ROTOR DRIVE COUPLING.

ROTOR BRITE GOOT EIITO.										
DART										
TAIL ROTOR DRIVE COUPLING										
LUBRICATION WORKAID										
DWG NO.		RBT1	8028		REV 1					
MAT'L DELRI HEAT TREAT FINISH SPEC DRAWN BY: CHECKED: OPPS APPR:	CLOUGH DUERFE	I LDT	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ±.5° .X ± .1 SURFACES = 125/ 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R -2. DIMENSIONAL LIMITS APPLY AFTER PLATING -3. INTERPRET DIM AND TOL PER							
QA APPR:	ANDLINGON		ASME Y14.5M-2009 USED ON MODEL							
APPROVED: GILBERT			BELL 412							
SCALE	1:2	DATE 3/2	23/2016	SHEET 1 OF	1					